

MODEL	250 STANDARD	250 FLEETSIDE	250 HO FLEETSIDE	250 HO FLEETSIDE SAFETY	250 HO HI-RIDER	250 HO LE	300 LX	300 LX
DRIVE CONFIGURATION	4X2	4X2	4X2	4X2	4X4	4X2	4X2	4X4
INTERIOR FEATURES								
Driver Footrest	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Air-Conditioner	-	Manual	Manual	Manual	Manual	Manual	Manual	Manual
Pollen Filter	-	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Inside Rear-View Mirror	Day / Night	Day / Night	Day / Night	Day / Night	Day / Night	Day / Night	Day / Night	Day / Night
Sunvisor	Driver and Passenger	Driver and Passenger	Driver and Passenger	Driver and Passenger	Driver and Passenger	Driver with Ticketholder and Passenger with Vanity Mirror	Driver with Ticketholder and Passenger with Vanity Mirror	Driver with Ticketholder and Passenger with Vanity Mirror
Digital Clock	Standard	Standard	Standard	Standard	Standard	--	-	-
Cruise Control	-	-	-	-	-	-	Standard	Standard
Multi-Information Display (MID)	-	-	-	-	-	-	Standard	Standard
Dashboard Illumination Control	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Auxiliary 12-V Power Socket	1	1	1	1	1	1	1	1
Lockable Glove Box	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Utility Box on Glove Box	Standard	Standard	Standard	Standard	Standard	Standard	Standard with Lid and Soft Pad and Black Garnish	Standard with Lid and Soft Pad and Black Garnish
Door Trim with Storage Pockets and Integrated Cupholders	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Floor Tunnel / Console with Integrated Cupholder	-	-	-	-	-	Standard	Standard	Standard
Centre Console Storage Box with Lid	-	-	-	-	Standard	Standard	Standard with Soft Armrest Pad	Standard with Soft Armrest Pad
Fuelflap Remote	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Window Operation	Manual – Front	Manual – Front	Manual – Front	Manual – Front	Power – Front, Driver One-Touch, Jam Protection	Power – Front, Driver One-Touch, Jam Protection and Timer	Power – Front, Driver One-Touch, Jam Protection and Timer	Power – Front, Driver One-Touch, Jam Protection and Timer
Rear Window	Fixed without Defogger	Fixed without Defogger	Fixed without Defogger	Fixed without Defogger	Fixed without Defogger	Sliding	Sliding	Sliding
INFOTAINMENT								
Audio System	Available	Available	Available	Available	AM/FM Radio, CD Player, USB, Clock, Bluetooth® – Audio Streaming & Hands-Free Phone	AM/FM Radio, Clock, Bluetooth® Audio/Hands-Free Phone, 8" Touchscreen	AM/FM Radio, Clock, Bluetooth® Audio/Hands-Free Phone, 8" Touchscreen	AM/FM Radio, Clock, Bluetooth® Audio/Hands-Free Phone, 8" Touchscreen
Audio Input Terminal: Auxiliary, iPod	-	-	-	-	Standard	Standard	Standard	Standard
USB Port (Music Playback and Device Link)	-	-	-	-	-	Front	Front	Front
USB Charge Ports	-	-	-	-	-	-	Front	Front
Speakers	Available (x 2)	Available (x 2)	Available (x 2)	Available (x 2)	2	4	4	4
Antenna	-	-	-	-	Standard	Standard	Standard	Standard
OPTIONS								
Front Bumper – Body Colour	Available	Available	Available	Available	-	-	-	-
16" Alloy Wheels & 205 / 70 R16C Tyres (All Terrain)	-	Available	-	-	-	-	-	-
16" Alloy Wheels & 245 / 70 R16C Tyres (All Terrain)	-	-	Available	Available	Available	-	-	-
18" Alloy Wheels & 255 / 60 R18 Tyres (All Terrain)	-	-	-	-	Available	Available	-	-
Sliding Rear Window	Available	Available	Available	Available	Available	-	-	-
Fixed Rear Window without Defogger	-	-	-	-	-	Available	Available	Available
Black Leather Interior	-	-	-	-	Available	Available	Available	Available
AM/FM Radio, Clock, Bluetooth® Audio Streaming/Hands-Free Phone, 8" Touchscreen	Available	-	-	-	Available	-	-	-
Rear Step Bumper with Integrated Towbar – End Caps with Black Finishing	-	-	-	-	Available	Available	-	-
Rear Step Bumper with Integrated Towbar (Heavy-Duty) and Rear Park-Assist – End Caps with Bright Finishing	-	-	-	-	-	-	Available	Available
Metallic Paint	Available	Available	Available	Available	Available	Available	Available	Available
WARRANTY / SERVICE INTERVALS								
Warranty	5 Years / 120 000 km	5 Years / 120 000 km	5 Years / 120 000 km	5 Years / 120 000 km	5 Years / 120 000 km	5 Years / 120 000 km	5 Years / 120 000 km	5 Years / 120 000 km
Anti-Corrosion Warranty	5 Years / Unlimited km	5 Years / Unlimited km	5 Years / Unlimited km	5 Years / Unlimited km	5 Years / Unlimited km	5 Years / Unlimited km	5 Years / Unlimited km	5 Years / Unlimited km
Service Plan	5 Years / 90 000 km	5 Years / 90 000 km	5 Years / 90 000 km	5 Years / 90 000 km	5 Years / 90 000 km	5 Years / 90 000 km	5 Years / 90 000 km	5 Years / 90 000 km
Service Intervals	12 Months / 15 000 km	12 Months / 15 000 km	12 Months / 15 000 km	12 Months / 15 000 km	12 Months / 15 000 km	12 Months / 15 000 km	12 Months / 15 000 km	12 Months / 15 000 km

(1) Fuel Economy & CO₂ data as per ECE R101 / SANS 20101 Regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions & the vehicle's equipment, condition & use.
(2) Payload – preliminary data shown for D-Max models.
(3) Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle & trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 & GA2) must not be exceeded. (e.g.: if a 3.0 L Diesel is towing 3.500 kg its Maximum Vehicle Mass is 2.500 kg in order to be within GCM). Date of print October 2018.

D-MAX-SERIES

Single Cab Spec Sheet

D-MAX



DURABILITY
RELIABILITY
CAPABILITY

www.isuzu.co.za f t

ISUZU
With you, for the long run

MODEL	250 STANDARD	250 FLEETSIDE	250 HO FLEETSIDE	250 HO FLEETSIDE SAFETY	250 HO HI-RIDER	250 HO LE	300 LX	300 LX
DRIVE CONFIGURATION	4X2	4X2	4X2	4X2	4X4	4X2	4X2	4X4
ENGINE								
Engine Code	4JA1L	4JA1L	4JK1TC HO	4JK1TC HO	4JK1TC HO	4JK1TC HO	4JJ1TC HO	4JJ1TC HO
Displacement (cc)	2499	2499	2499	2499	2499	2499	2999	2999
No. of Cylinders	4	4	4	4	4	4	4	4
Compression Ratio	18.5:1	18.5:1	18.1:1	18.1:1	18.1:1	18.1:1	17.3:1	17.3:1
Bore X Stroke (mm)	93 X 92	93 X 92	95.4 X 87.4	95.4 X 87.4	95.4 X 87.4	95.4 X 87.4	95.4 X 104.9	95.4 X 104.9
No. of Valves	8	8	16	16	16	16	16	16
Power (kW) @ r/min	58 @ 3900	58 @ 3900	100 @ 3400	100 @ 3400	100 @ 3400	100 @ 3400	130 @ 3600	130 @ 3600
Torque (Nm) @ r/min	176 @ 1800	176 @ 1800	320 @ 1800 - 2800	320 @ 1800 - 2800	320 @ 1800 - 2800	320 @ 1800 - 2800	380 @ 1800 - 2800	380 @ 1800 - 2800
Turbocharger	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Intercooler	-	-	Standard	Standard	Standard	Standard	Standard	Standard
FUEL CONSUMPTION⁽¹⁾								
Combined Cycle (l/100 km)	7.9	7.9	7.6	7.6	8.2	7.6	7.7	8.2
Combined CO ₂ Emissions (g/km)	208	208	199	199	217	199	203	215
Fuel Type	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
TRANSMISSION								
Transmission Type	5-Speed Manual	5-Speed Manual	5-Speed Manual	5-Speed Manual	5-Speed Manual	5-Speed Manual	6-Speed Manual	6-Speed Manual
Gear Ratio: 1st	4.357	4.357	4.008	4.008	4.008	4.008	4.942	4.942
Gear Ratio: 2nd	2.502	2.502	2.301	2.301	2.301	2.301	2.43	2.43
Gear Ratio: 3rd	1.501	1.501	1.427	1.427	1.427	1.427	1.428	1.428
Gear Ratio: 4th	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Gear Ratio: 5th	0.809	0.809	0.744	0.744	0.744	0.744	0.749	0.749
Gear Ratio: 6th	-	-	-	-	-	-	0.634	0.634
Gear Ratio: Reverse	3.97	3.97	3.651	3.651	3.651	3.651	4.597	4.597
4WD Selector Switch	-	-	-	-	Standard	-	-	Standard
Low Range Ratio	-	-	-	-	2.482	-	-	2.482
FRONT DIFFERENTIAL								
Shift on the Fly up to 100 km/h	-	-	-	-	Standard	-	-	Standard
Axle Ratio: Final Drive	-	-	-	-	4.1	-	-	3.727
REAR DIFFERENTIAL								
Differential Lock	Available	Available	Available	Available	Standard	Standard	Standard	Standard
Axle Ratio: Final Drive	4.555	4.555	4.1	4.1	4.1	4.1	3.727	3.727
CHASSIS DESIGN								
Front Wheel Suspension	Coil Over Shock	Coil Over Shock	Coil Over Shock	Coil Over Shock	Coil Over Shock	Coil Over Shock	Coil Over Shock	Coil Over Shock
Rear Wheel Suspension	Leaf-Spring Underslung	Leaf-Spring Overslung	Leaf-Spring Overslung	Leaf-Spring Overslung	Leaf-Spring Overslung	Leaf-Spring Overslung	Leaf-Spring Overslung	Leaf-Spring Overslung
Shock Absorbers	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Suspension	Low-Ride	High-Ride	High-Ride	High-Ride	High-Ride	High-Ride	High-Ride	High-Ride
Skid Plate Guard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Engine Sump Guard	-	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Transfer Case Guard	-	-	-	-	Standard	-	-	Standard
WHEELS / TYRES								
Tyre Size	215 / 70 R16C	205 / 70 R16C	205 / 70 R16C	245 / 70 R16C	245 / 70 R16	245 / 70 R16C	255 / 60 R18 AT	255 / 60 R18 AT
Wheel Size / Type	16" X 6.5J-41 Steel	16" X 6.5J-33 Steel	16" X 6.5J-33 Steel	16" X 6.5J-33 Steel	16" X 6.5J-33 Steel	16" X 7.0J-33 Alloy	18" X 7.5J Alloy	18" X 7.5J Alloy
Spare Wheel	16" X 6.5J-41 Steel	16" X 6.5J-33 Steel	16" X 6.5J-33 Steel	16" X 6.5J-33 Steel	16" X 6.5J-33 Steel	16" X 6.5J-33 Steel	18" X 7.5J Alloy	18" X 7.5J Alloy
Turning Circle: Curb-to-Curb (m)	12.2	12.8	12.8	12.8	12.8	12.8	12.8	12.8
DIMENSIONS								
Length (mm)	5218	5218	5218	5218	5314	5314	5314	5314
Width (mm)	1860	1860	1860	1860	1860	1860	1860	1860
Height (mm)	1690	1790	1790	1790	1790	1790	1790	1790
Wheelbase (mm)	3095	3095	3095	3095	3095	3095	3095	3095
Front / Rear Track (mm)	1510 / 1510	1570 / 1570	1570 / 1570	1570 / 1570	1570 / 1570	1570 / 1570	1570 / 1570	1570 / 1570
Rear Overhang (mm)	1225	1225	1225	1225	1321	1321	1321	1321
Ground Clearance (mm)	200	200	225	225	225	225	220	220
Loadbox Length (mm)	2305	2305	2305	2305	2305	2305	2305	2305
Loadbox Width (mm)	1535	1535	1535	1535	1535	1535	1535	1535
Loadbox Depth (mm)	445	445	445	445	445	445	445	445
Approach Angle (°)	-	-	-	-	30.0	-	-	30.0
Departure Angle (°)	-	-	-	-	22.4	-	-	22.4
Breakover Angle (°)	-	-	-	-	22.4	-	-	22.4
Wading Depth (mm)	-	-	-	-	600	-	-	600
MASS / CAPACITIES								
Gross Vehicle Mass (GVM) (kg)	2850	2850	3000	3000	3000	3000	3100	3100
Gross Combined Mass (GCM) (kg)	4450	4450	5000	5000	5000	5000	6000	6000
Tare Mass (kg)	1620	1660	TBD	1710	1835	1740	1810	1905
Payload (kg) ⁽²⁾	1186	1137	TBD	1235	1112	1213	1238	1141
Towing Capacity (kg): Unbraked ⁽³⁾	750	750	750	750	750	750	750	750
Towing Capacity (kg): Braked ⁽³⁾	1600	1600	2000	2000	2000	2000	2900	2900
Fuel Tank Capacity (Litres)	80	80	80	80	80	80	80	80

(1) Fuel Economy & CO₂ data as per ECE R101 / SANS 20101 Regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions & the vehicle's equipment, condition & use.

(2) Payload – preliminary data shown for D-Max models.

(3) Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle & trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 & GA2) must not be exceeded. (e.g.: if a 3.0 L Diesel is towing 3.500 kg its Maximum Vehicle Mass is 2.500 kg in order to be within GCM). Date of print October 2018.

MODEL	250 STANDARD	250 FLEETSIDE	250 HO FLEETSIDE	250 HO FLEETSIDE SAFETY	250 HO HI-RIDER	250 HO LE	300 LX	300 LX
DRIVE CONFIGURATION	4X2	4X2	4X2	4X2	4X4	4X2	4X2	4X4
LOADBOX FEATURES								
Tiedown Brackets in Loadbox for Load Restraint	4	4	4	4	4	4	4	4
Rope Hooks on Loadbox Side	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
SAFETY FEATURES								
Load-Sensing Proportioning Valve (LSPV)	Standard	Standard	Standard	-	-	-	-	-
Anti-Lock Braking System (ABS)	-	-	-	Standard	Standard	Standard	Standard	Standard
Electronic Brake-Force Distribution (EBD)	-	-	-	Standard	Standard	Standard	Standard	Standard
Brake-Assist System (BAS)	-	-	-	Standard	Standard	Standard	Standard	Standard
Electronic Stability Control (ESC) with Traction Control	-	-	-	Standard	Standard	Standard	Standard	Standard
Hill-Start Assist (HSA)	-	-	-	Standard	Standard	Standard	Standard	Standard
Hill Descent Control (HDC)	-	-	-	Standard	Standard	Standard	Standard	Standard
Trailer Sway Control	-	-	-	-	-	-	Standard	Standard
Brake Override System (BOS)	-	-	-	-	-	-	Standard	Standard
Side-Impact Protection Bars	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Height-Adjustable 3-Point Seatbelts	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Front Seat Centre Lapbelt (2-Point)	Standard	Standard	Standard	Standard	-	-	-	-
Seatbelt Pre-Tensioners	-	-	-	Standard	Standard	Standard	Standard	Standard
Driver & Passenger Airbags	-	-	-	Standard	Standard	Standard	Standard	Standard
Collapsible Steering Column	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Speed-Sensitive Door Lock	-	-	-	-	-	-	Standard	Standard
Park Distance Control (PDC)	-	-	-	-	-	-	Rear	Rear
Warning Triangle Kit	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
SECURITY FEATURES								
Manual Door Locks	Standard	Standard	Standard	Standard	-	-	-	-
Remote-Controlled Central Locking	-	-	-	-	Standard	Standard	Standard	Standard
Remote Keyless Entry	-	-	-	-	Standard, Non-Integrated FOB	Standard, Integrated FOB	Standard, Integrated FOB	Standard, Integrated FOB
Anti-Theft Alarm System	Alarm Ready	Alarm Ready	Alarm Ready	Alarm Ready	Standard, Door-Activated	Standard	Standard	Standard
Ultrasonic Alarm	-	-	-	-	-	Standard	Standard	Standard
Transponder Immobiliser System	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
INTERIOR / EXTERIOR LIGHTING								
Interior Courtesy Lamps	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Illuminated Entry	-	-	-	-	Standard	Standard	Standard	Standard
Fog Lamps	-	-	-	-	-	Front	Front	Front
Daytime Running Lights (DRL)	-	-	-	-	-	-	LED	LED
Headlamps	Halogen	Halogen	Halogen	Halogen	Halogen	Halogen	Projector	Projector
Headlamps 'ON' Warning Buzzer	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Side Indicator Lamp on Door	Standard	Standard	Standard	Standard	Standard	Standard	-	-
Rear Taillamps – Combination	Bulb	Bulb	Bulb	Bulb	Bulb	Bulb	LED	LED
Centre High-Mounted Stoplamp	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
EXTERIOR FEATURES								
Radiator Grille – Colour	Grey	Grey	Grey	Grey	Grey	Grey	Anthracite	Chrome
Front Bumper – Colour	Black	Black	Black	Black	Black	Body Colour	Body Colour	Body Colour
Rear Bumper – Colour	-	-	-	-	-	Black	Black	Chrome
Exterior Door Handles – Colour	Black	Black	Black	Black	Black	Black	Body Colour	Chrome
Exterior Mirrors	Black – Manual Adjustment	Black – Manual Adjustment	Black – Manual Adjustment	Black – Manual Adjustment	Black – Manual Adjustment	Black – Power Adjustment	Body Colour – Power Adjustment, Side Indicator, Driver Side Aspherical	Chrome – Power Adjustment and Folding, Side Indicator, Driver Side Aspherical
Black Side-Steps	-	-	-	-	-	-	-	Standard
Mudflaps	Front and Rear	Front and Rear	Front and Rear	Front and Rear	Front and Rear	Front and Rear	Front and Rear	Front and Rear
Wipers	Intermittent	Intermittent	Intermittent	Intermittent	Intermittent	Intermittent	Intermittent	Variable Intermittent
Fog Lamp Bezel	-	-	-	-	-	-	Chrome	Chrome
INTERIOR FEATURES								
Power-Assisted Steering (PAS)	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Standard	Standard	Hydraulic
Steering Column Adjustment	Tilt	Tilt	Tilt	Tilt	Tilt	Tilt	Tilt	Tilt
Steering Wheel Material	Urethane	Urethane	Urethane	Urethane	Urethane	Urethane	Leather-Wrapped	Leather-Wrapped
Multi-Function Controls	-	-	-	-	-	-	Audio	Audio and Auto Cruise
Interior Door Handles – Colour	Black	Black	Black	Black	Black	Black	Black	Chrome
Gearknob Trim	Standard	Standard	Standard	Standard	Standard	Urethane	Urethane	Urethane & Chrome
Front Seat Configuration	60:40-Split Bench Cushion	60:40-Split Bench Cushion	60:40-Split Bench Cushion	60:40-Split Bench Cushion	60:40-Split Bench Cushion	2 x Bucket Seats, Deluxe Pad	2 x Bucket Seats, Deluxe Pad	2 x Bucket Seats, Deluxe Pad
Seat Trim	Canvas	Canvas	Canvas	Canvas	Canvas	Cloth	Cloth	Cloth
Seat Adjustment	-	-	-	-	-	Driver – Manual Height, Reclining	Driver – Manual Height, Reclining	Driver – Manual Height, Reclining
Floor Trim	Vinyl with Heel Mats (x 2)	Vinyl with Heel Mats (x 2)	Vinyl with Heel Mats (x 2)	Vinyl with Heel Mats (x 2)	Vinyl with Heel Mats (x 2)	Vinyl with Heel Mats (x 2)	Carpet with Heel Mat (x 1)	Carpet with Heel Mat (x 1)

